



PERMIT APPLICATION SUBMITTAL REQUIREMENTS

Rule 6 – Erosion Control Exhibits and Information

The following exhibits and information must accompany the permit application. One set, full size; one set, reduced to 11"x17"; and a copy of all submittals in electronic .pdf format.

- An existing and proposed topographic map which clearly shows contour elevations with at least 2-foot contour intervals on and adjacent to the land, property lines, all hydrologic features, the proposed land disturbing activities, and the locations of all runoff, erosion and sediment controls and soil stabilization measures.
- Existing soils map for the site.
- Plans and specifications for all proposed runoff, erosion and sediment controls, and temporary and permanent soil stabilization measures.
 1. Temporary erosion and sediment control measures which will remain in place until permanent vegetation is in place shall be identified.
 2. Permanent erosion and sediment control measures such as emergency overflow swales shall be identified.
 3. Erosion and/or sediment control at the perimeter of surface stormwater facilities between the normal water level (NWL) and the 100-year high water level (HWL). This is typically accomplished with silt fence, erosion control blanket or biorolls.
 4. Energy dissipation (riprap) at all stormsewer outlets.
 5. Sediment control at all construction entrances and exits (rock construction entrance and exit).
 6. Sediment control at all stormsewer inlets. Straw bales and silt fence surrounding inlets are not acceptable.
- Detailed schedules for implementation of the land disturbing activity, the erosion and sediment controls, and soil stabilization measures.
- Plans and specifications for dewatering methods and outlet of stormwater.
- Detailed description of the methods to be employed for monitoring, maintaining, and removing the erosion and sediment controls, and soil stabilization measures. The name, address and phone number of the person(s) responsible shall also be provided.
- For projects over one acre of disturbed area, documentation that the project applicant has applied for a NPDES General Construction Permit shall be submitted as well as the Stormwater Pollution Prevention Plan (SWPPP) prepared for the NPDES permit.
- Bioretention and infiltration areas must be enclosed by fencing or otherwise protected from disturbance prior to the start of the land disturbing activity if the land is not mass graded. If the site is mass graded, the existing soil profile of biofiltration and infiltration areas (prior to the addition of any soil amendments) must be ripped or scarified to a depth of at least 18".